



GRP Dormers



Barn Owl 005 GRP Flat Top Dormer



Specification:

Flat top complete dormer unit with lead effect side cheeks and top, fascia and soffit can be finished in grey or white.

The unit is insulated and has a bonded timber sub frame ready for the fixing of plasterboard. It is fixed to the roof via a drainage flange which is screwed to the rafters then covered with felt and battens.

NB: This dormer would be 3 sided and would rest on the eaves.

Dimensions:

Dormer	Drg Ref	Roof Pitch	Window Opening	
			Width	Height
Barn Owl 005	055	40°	915mm	1050mm

Contact Us:

M: 07760 711127

T: 01242 430349

E: sales@bricks-tiles.co.uk

Web: www.bricks-tiles.co.uk

Tawny Owl 001 GRP Apex Dormer



Specification:

Apex dormer with gable front and lead effect cheeks. Fascia and soffit can be finished in white or lead effect.

Supplied with timber roof trusses ready for tiling on site.

The unit is insulated and has a bonded timber sub frame ready for the fixing of plasterboard.

It is fixed to the roof via a drainage flange which is screwed to the rafters then covered with felt and battens.

Dimensions:

Dormer	Drg Ref	Roof Pitch	Window Opening	
			Width	Height
Tawny Owl 001	Ex03	40°	900mm	1050mm

Contact Us:

M: 07760 711127

T: 01242 430349

E: sales@bricks-tiles.co.uk

Web: www.bricks-tiles.co.uk

Tawny Owl 002
GRP Apex Dormer



Specification:

Apex dormer with gable front and lead effect cheeks. Fascia and soffit can be finished in white or lead effect.

Supplied with timber roof trusses ready for tiling on site.

The unit is insulated and has a bonded timber sub frame ready for the fixing of plasterboard.

It is fixed to the roof via a drainage flange which is screwed to the rafters then covered with felt and battens.

Dimensions:

Dormer	Drg Ref	Roof Pitch	Window Opening	
			Width	Height
Tawny Owl 002	Ex06	50°	900mm	1050mm

Contact Us:

M: 07760 711127

T: 01242 430349

E: sales@bricks-tiles.co.uk

Web: www.bricks-tiles.co.uk

Tawny Owl 004
GRP Apex Dormer



Specification:

Apex half dormer with decorative gable front and lead effect cheeks. Fascia and soffit can be finished in white or lead effect.

Supplied with timber roof trusses ready for tiling on site.

The unit is insulated and has a bonded timber sub frame ready for the fixing of plasterboard.

It is fixed to the roof via a drainage flange which is screwed to the rafters then covered with felt and battens.

Dimensions:

Dormer	Drg Ref	Roof Pitch	Window Opening	
			Width	Height
Tawny Owl 004	Ex30	35°	1200mm	1200mm

Contact Us:

M: 07760 711127

T: 01242 430349

E: sales@bricks-tiles.co.uk

Web: www.bricks-tiles.co.uk

Tawny Owl 005
GRP Apex Dormer



Specification:

Apex dormer with gable front and lead effect cheeks. Fascia and soffit can be finished in white or lead effect.

Supplied with timber roof trusses ready for tiling on site.

The unit is insulated and has a bonded timber sub frame ready for the fixing of plasterboard.

It is fixed to the roof via a drainage flange which is screwed to the rafters then covered with felt and battens.

Dimensions:

Dormer	Drg Ref	Roof Pitch	Window Opening	
			Width	Height
Tawny Owl 005	Ex37	35°	1210mm	1210mm

Contact Us:

M: 07760 711127

T: 01242 430349

E: sales@bricks-tiles.co.uk

Web: www.bricks-tiles.co.uk

Tawny Owl 011 GRP Apex Dormer



Specification:

Apex dormer with gable front and lead effect cheeks. Fascia and soffit can be finished in white or lead effect.

Supplied with timber roof trusses ready for tiling on site.

The unit is insulated and has a bonded timber sub frame ready for the fixing of plasterboard

It is fixed to the roof via a drainage flange which is screwed to the rafters then covered with felt and battens.

Dimensions:

Dormer	Drg Ref	Roof Pitch	Window Opening	
			Width	Height
Tawny Owl 011	063	45°	915mm	1200mm

Contact Us:

M: 07760 711127

T: 01242 430349

E: sales@bricks-tiles.co.uk

Web: www.bricks-tiles.co.uk

Tawny Owl 027 GRP Apex Dormer



Specification:

Apex dormer with gable front and lead effect cheeks. Fascia and soffit can be finished in white or lead effect.

Supplied with timber roof trusses ready for tiling on site.

The unit is insulated and has a bonded timber subframe ready for the fixing of plasterboard

It is fixed to the roof via a drainage flange which is screwed to the rafters then covered with felt and battens.

Dimensions:

Dormer	Drg Ref	Roof Pitch	Window Opening	
			Width	Height
Tawny Owl 027	217	45°	1200mm	1050mm

Contact Us:

M: 07760 711127

T: 01242 430349

E: sales@bricks-tiles.co.uk

Web: www.bricks-tiles.co.uk